



- NOTE:**
- PONTOON IS DESIGNED IN ACCORDANCE WITH AS 3962-1991 GUIDELINES FOR DESIGN OF MARINAS. RESTRICTED ACCESS.
 - ALL WELDING IN ACCORDANCE WITH AS 1665-1992. WELDING OF ALUMINIUM STRUCTURES.
 - ALL STRUCTURE IS FULLY WELDED WITH A NOMINAL FILLET OF 5mm
 - ALL EXTRUSIONS ARE OF GRADE 6063-T5 OR EQUIVALENT.
 - FILLER ALLOY IS GRADE 5356
 - ALL TIMBER IS TO BE TREATED WITH A SUITABLE PRESERVATIVE. (CREOSOTE, DECKING OIL ETC)
 - ALL FASTENERS ARE CORROSION RESISTANT STAINLESS STEEL.
 - ALL EXPOSED BOLTS ARE TO BE RECESSED INTO THE TIMBER BY COUNTER BORING.
 - ALL BOLT THREADS ARE TO BE TREATED WITH ANTI-SIEZE OR EQUIVALENT LUBRICATING COMPOUND, PRIOR TO FASTENING.

APPROX. WEIGHT-850kg

**MARINE DOCK SYSTEMS
PTY LTD**

5.0m x2.55m PONTOON
INBUILT PILE GUIDE
4x 1200L FLOATS

PONTOON-2939



SCALE	N.T.S.	DWG	A4-2939	
DRAWN	JPM	REV	A	27,10,00
DATE	20,8,03	CHK		APP'D